



Harness Dickey & Pierce PLC  
Attorneys and Counselors  
5445 Corporate Drive, Suite 200  
Troy, Michigan 48098-2683  
Phone: 248-641-1600 Fax: 248-641-0270  
Metropolitan: Detroit St. Louis Washington, DC

DATE: October 9, 2009

NO. OF PAGES (INCLUDING THIS PAGE): 2

FOR: Examiner Erin L. Colello

COMPANY: USPTO

FAX NO.: (571) 270-4212

PHONE:

ORIGINAL WILL FOLLOW BY:

☐ REGULAR MAIL☐ OVERNIGHT MAIL☐ COURIER☒ WILL NOT FOLLOW

FROM: Michael L. Taylor, Reg. No. 50521

Please let us know by phone or fax if you do not receive any of these pages.

## COMMENTS:

Application No.: 10/801,906  
HDP Ref. No. 5074A-000010/DVB

**NOTICE**

The information contained in this fax transmission is intended only for the individual to whom or entity to which it is addressed. It may also contain privileged, confidential, attorney work product or trade secret information which is protected by law. If the reader of this message is not the intended recipient, or an employee or agent responsible for delivering the message to the addressee, the reader is hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please immediately notify us by telephone and return the original message to us at the address above via the U.S. Postal Service. We will reimburse you for any reasonable expense (including postage) for the return of the original message.

**PATENT****IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application No.: 10/801,906  
Filing Date: March 16, 2004  
Applicant: Anthony J. Melkent et al.  
Group Art Unit: 3734  
Examiner: Erin L. Colello  
Title: MULTIPLE CANNULA IMAGE GUIDED TOOL FOR  
IMAGE GUIDED PROCEDURES  
Attorney Docket: 5074A-000010/DVB

---

**Interview Outline**

1. A tracking device that can be positioned on a frame for tracking multiple cannulas throughout a procedure.
2. A tracking device can be connected to continually/actively track the cannulas throughout a procedure.
3. A structure can be used to maneuver the cannulas.
4. A structure to manipulate the cannulas can be handle held, and possibly specifically pistol grip/shaped.
5. A tracking device connector structure as illustrated in Figs.

15100420 1